



ZHEJIANG HANGCHA IMP. & EXP. CO., LTD.

Factory site: 666 Xiangfu Road,
Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755
Fax: +86-571-88926789 88132890

sales@hcforklift.com
www.hcforklift.com



Follow us on
Facebook



Follow us on
YouTube



Follow us on
WeChat



ISO14001:2015



ISO9001:2015



HANGCHA trucks conform
to the European Safety
Requirements.

2018 VERSION 2/COPYRIGHT 2018/08

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.



X Series Diesel / Gasoline / LPG Counterbalanced Forklift Trucks

with capacities of 1,500 to 3,800kg

The World of Hangcha



X Series

Diesel / Gasoline / LPG
Counterbalanced
Forklift Trucks



Innovation design

The X series is the new series of internal combustion counterbalance forklift truck developed by Hangcha independently, adopting the world advanced technologies based on the original products. Through the comprehensive upgrading of appearance molding, energy conservation, environmental friendly, comfort, security and reliability, it will become the world-class forklift truck which can meet your overall demands.

Strong appearance and visual impact

The appearance of full truck is developed under the cooperation with professional industrial design company by adopting the appearance design methods of brand-new concept. The streamlined surface modeling design brings smooth lines, elegant appearance, vigorous and steady surface as well as the outstanding inherence, possessing the powerful visual impact.

The truck is small, exquisite and concise. which adopting the newly designed parts with opening mould at large area, the appearance of full vehicle will be more humanized.



The new designed mast increase forward visibility 15%



Noise ↓ 3dB



Legroom ↑ 30%



High pressure common rail electronic-controlled engine provide lower failure rate (Common rail engine)



Floating structure decrease the vibration by 10%



Exhaust emission ↓ 35% (Common rail engine)



Grade-speed ability ↑ 10% (Common rail engine)



Aluminous plate-fin radiator provides stronger structure



Prolong the service life of steering axle 20%



Fuel consumption ↓ 10% (Common rail engine)



Better cold starting performance (Common rail engine)



Water temp ↓ 10 C, oil temp ↓ 10%

Energy conservation and Environmental friendly



The high pressure common rail electronic-controlled engine which adopts high pressure multiple injections technology to ensure the strong power take-off, lower emission and better cold starting performance; saving the 10% of energy consumption.



The whole truck adopts LED lights as shiner and new-type panoramic retroreflector to ensure energy conservation and power saving as well as greatly improve the performance and service life of luminaires at the same time.

The truck all adopt the environmental friendly material to reduce environmental hazards.

Maintenance

Integral locking pin structure on the hood can be opened without tool, which is convenient for daily repair and maintenance.



Adoption of new generation integrated electric box makes maintenance and repair convenient, layout becomes more reasonable and with better water-proof performance.

The enlarged opening angle of hood and increase of left and right hood side plates can provide you with convenient and rapid maintenance mode.



Newly-developed LCD instrument has more comprehensive functions and more stable performance and entirely displays the full truck state, fault code and other important information, which can make the operator more intuitively and conveniently have a better knowledge of truck state and make the maintenance conveniently.

Fully improved reliability And security



1. The radiator adopts aluminous plate-fin radiator with better performance and higher structural strength independent oil radiator, optimized oil and water heat dissipation channel and double ventilation holes on counterweight can greatly improve cooling efficiency and reliability of overloaded operation and ensure reliable operation of the engine.

2. 2.0~3.8t roller bearing on the steering axle king pin adopts large size tapered roller bearing (TRB), larger steering cylinder and bumper block assemblies on the top, which can prolong the service life of bearing and highly improve the reliability of steering axle.

3. Overhead guard adopts special-shaped steel tube, which can reinforce the strength and improve sealing of the cab.

4. Optimized hydraulic breather structure and integrated with return oil filter can prolong the service life of hydraulic pressure system.



Comfort

Option of the most advanced full floating structure in the world can minimize the vibration of full truck and support more superior buffer, micro-motion and starting functions at the same time. With several imported engines, they can constitute more perfect engine-transmission system.


Reduce the caster angle of instrument stand and adopt the integral hood to greatly increase the space underfoot; The orthodrome of overhead guard fore leg will expand the driving space;



Adopt the new-type of box iron. Increase the inside width of inner mast and the spacing between lifting cylinders. The lowering of instruments in the cabin will greatly increase the forward visibility; The rear visibility will also be greatly improved through the optimization design of counterweight.



The design of steering wheel of small diameter and electro-hydraulic reversing as well as the car-type double-handle combination switch will greatly improve the driving comfort.



Optimized air intake and exhaust system, high-capacity exhaust silencer and high-effect intake muffler will reduce the noise of full truck by 3dB and reduce the vibration by 20%.



Intelligentized management system (option)

Reserved plug of extending function of Intelligent module is on the wire bundles that makes truck management more convenient and rapid.

Standard Specification

- / Cover of tilt cylinder
- / Traction device
- / LED working light
- / Hydraulic oil filter
- / Electric Flameout
- / Seat with belt
- / Skidproof pedal
- / Air filter
- / Hydraulic oil dipstick
- / Mast speed limiting valve
- / Full hydraulic power steering
- / Wide view duplex mast
- / Standard forks
- / Waterproof cover on the guard
- / Standard overhead guard
- / Rear combination LED light
- / Panoramic rearview mirror
- / Filf folder
- / Adjustable steering column
- / Pre-heating indicator
- / Engine fuel pressure warning
- / Neutral switch
- / Engine hood spring
- / Dipstick
- / Pneumatic tyres
- / Standard load backrest
- / Horn
- / Fuel gauge
- / LCD display
- / Cable parking brake
- / Tilt cylinder self-locking valve
- / Fork carriage mounting class II(III)
- / Timer
- / Load safety valve
- / Charging indicator
- / Water temperature gauge
- / Toolbox
- / Reversing buzzer
- / Return oil filter
- / Hand grip
- / Integrated controller
- / Oil-water separator
- / Engine fault warning
- / Rubber pedal
- / 2nd hydraulic function
- / Transmission oil temperature warning
- / Dynamic load sensing system (for desel engine)

Optional Mast

- / Duplex wide view full free mast
- / Trilex wide view full free mast
- / Special duplex wide view mast
- / Wider fork carriage
- / Special forks

Options

- / Dual driving wheel
- / Cabin
- / High-positioned exhaust system
- / Customer painting
- / Cabin heater
- / LED rear working light
- / Hood lock
- / Double heat insulating pad and leather cover
- / Net cover of radiator
- / Solid tyre
- / Non-mark tyre (white/green)
- / Middle-positioned exhaust system
- / Sparkle arrester
- / Suspension seat
- / Purified exhaust system
- / Fuel tank lock
- / Speed meter
- / Auxilliary hydraulic valve
- / Extinguisher
- / Reversing assist grip with horn button
- / Counter weight net
- / Height of overhead guard
- / Dual air filter
- / Milometer
- / Speed limiter (Electronic-Controlled engine)
- / Emergency switch
- / Fan protector
- / Over-speed alarm
- / Warning light
- / OPS system

Optional Attachments

- / Paper roll clamp
- / Rotating bale clamp
- / Load stabilizer
- / Multi-drum clamp
- / Bale clamp
- / Drum clamp
- / Dumping clamp
- / Crane arm
- / String pole
- / Weigher system
- / Sideshifter
- / Rotating forks
- / Fork extensioner
- / Load release device
- / Carton clamp
- / Push-pull device
- / Bucket
- / Hook
- / Lengthened fork

1.5-1.8t X series mast:(Pneumatic)

Type	Model	Max. fork height	Overall height				Free lift		Front Overhang		Tilt range F/R (°)	Capacity Load capacity at 500mm			
			Lowered	Extended		Without backrest	With backrest	1.5t	1.75t	Single tire		Dual tire			
				Without backrest	With backrest					1.5t		1.75t	1.5t	1.75t	
															mm
Wide view mast	XR15/18M200	2000	1495	2658	2955	155	155	405	410	6/6	1500	1750	1500	1750	
	XR15/18M250	2500	1745	3158	3455	155	155	405	410	6/12	1500	1750	1500	1750	
	XR15/18M270	2700	1845	3358	3655	155	155	405	410	6/12	1500	1750	1500	1750	
	XR15/18M300	3000	1995	3658	3955	155	155	405	410	6/12	1500	1750	1500	1750	
	XR15/18M330	3300	2145	3958	4255	155	155	405	410	6/12	1500	1750	1500	1750	
	XR15/18M360	3600	2345	4258	4555	155	155	405	410	6/12	1500	1750	1500	1750	
	XR15/18M400	4000	2595	4658	4955	155	155	405	410	6/12	1400	1650	1500	1750	
	XR15/18M430	4300	2745	4958	5255	155	155	405	410	6/6	1300	1550	1400	1650	
	XR15/18M450	4500	2845	5158	5455	155	155	405	410	6/6	1250	1450	1350	1550	
	XR15/18M480	4800	2995	5458	5755	155	155	405	410	6/6	1100	1250	1200	1350	
Wide view full free duplex mast	XR15/18U250	2500	1760	3445	3184	1076	815	428	433	6/12	1500	1750	1500	1750	
	XR15/18U270	2700	1860	3645	3384	1176	915	428	433	6/12	1500	1750	1500	1750	
	XR15/18U300	3000	2010	3945	3684	1326	1065	428	433	6/12	1500	1750	1500	1750	
	XR15/18U330	3300	2160	4245	3984	1476	1215	428	433	6/12	1500	1750	1500	1750	
	XR15/18U360	3600	2310	4545	4284	1626	1365	428	433	6/12	1500	1750	1500	1750	
	XR15/18U400	4000	2560	4945	4684	1876	1615	428	433	6/12	1400	1650	1500	1750	
	XR15/18N400	4000	1960	4694	4955	1276	1015	428	433	6/6	1300	1550	1400	1650	
	XR15/18N430	4300	2060	4994	5255	1376	1115	445	450	6/6	1250	1450	1350	1550	
	XR15/18N450	4500	2110	5194	5455	1426	1165	445	450	6/6	1200	1350	1300	1450	
	XR15/18N480	4800	2260	5494	5755	1576	1315	445	450	6/6	1100	1250	1200	1350	
Wide view full free triplex mast	XR15/18N500	5000	2360	5694	5955	1676	1415	445	450	6/6	1050	1150	1150	1250	
	XR15/18N550	5500	2560	6194	6455	1876	1615	445	450	3/6	/	/	950	1050	
	XR15/18N600	6000	2810	6694	6955	2126	1865	445	450	3/6	/	/	750	850	

With sideshifter minus 150kg,with integral sideshifter minus 100kg.

2.0-2.5t X series mast:(Pneumatic)

Type	Model	Max. fork height	Overall height				Free lift		Front Overhang		Tilt range F/R (°)	Capacity Load capacity at 500mm			
			Lowered	Extended		Without backrest	With backrest	2.0t	2.5t	Single tire		Dual tire			
				Without backrest	With backrest					2.0t		2.5t	2.0t	2.5t	
															mm
Wide view mast	XR25M250	2500	1749	3207	3546	160	160	460	460	6/12	2000	2500	2000	2500	
	XR25M270	2700	1849	3407	3746	160	160	460	460	6/12	2000	2500	2000	2500	
	XR25M300	3000	1999	3707	4046	160	160	460	460	6/12	2000	2500	2000	2500	
	XR25M330	3300	2149	4007	4346	160	160	460	460	6/12	2000	2500	2000	2500	
	XR25M360	3600	2349	4307	4646	160	160	460	460	6/12	2000	2500	2000	2500	
	XR25M400	4000	2599	4707	5046	160	160	460	460	6/12	1900	2300	2000	2500	
	XR25M430	4300	2749	5007	5346	160	160	460	460	6/6	1800	2100	1950	2450	
	XR25M450	4500	2849	5207	5546	160	160	460	460	6/6	1700	2000	1900	2400	
	XR25M480	4800	2999	5507	5846	160	160	460	460	6/6	1500	1700	1700	2100	
	XR25M500	5000	3099	5707	6046	160	160	460	460	6/6	1400	1600	1600	2500	
Wide view full free duplex mast	XR25M550	5500	3349	6207	6546	160	160	460	460	3/6	1050	1200	1500	1800	
	XR25M600	6000	3599	6707	7046	160	160	460	460	3/6	700	800	1400	1600	
	XR25U250	2500	1764	3179	3518	1025	619	470.5	470.5	6/12	2000	2500	2000	2500	
	XR25U270	2700	1864	3379	3718	1125	719	470.5	470.5	6/12	2000	2500	2000	2500	
	XR25U300	3000	2014	3679	4018	1225	819	470.5	470.5	6/12	2000	2500	2000	2500	
	XR25U330	3300	2164	3979	4318	1325	919	470.5	470.5	6/12	2000	2500	2000	2500	
	XR25U360	3600	2314	4279	4618	1425	1019	470.5	470.5	6/12	2000	2500	2000	2500	
	XR25U400	4000	2564	4679	5018	1525	1119	470.5	470.5	6/12	1900	2300	2000	2500	
	XR25N400	4000	1964	4739	5078	1285	918	477.5	477.5	6/6	1800	2100	1950	2450	
	XR25N430	4300	2064	5039	5378	1385	1018	477.5	477.5	6/6	1700	2000	1900	2400	
Wide view full free triplex mast	XR25N450	4500	2114	5239	5578	1435	1068	477.5	477.5	6/6	1600	1900	1800	2300	
	XR25N480	4800	2264	5539	5878	1535	1168	477.5	477.5	6/6	1500	1700	1700	2100	
	XR25N500	5000	2364	5739	6078	1635	1268	477.5	477.5	6/6	1400	1600	1600	2000	
	XR25N550	5500	2564	6239	6578	1835	1468	477.5	477.5	3/6	1050	1200	1500	1800	
	XR25N600	6000	2814	6739	7078	2135	1768	477.5	477.5	3/6	700	800	1400	1600	
	XR25N650	6500	3014	7239	7578	2335	1968	477.5	477.5	3/6	/	/	1450	1300	
	XR25N700	7000	3264	7764	8104	2500	2218	477.5	477.5	3/6	/	/	1300	1200	

With sideshifter minus 150kg,with integral sideshifter minus 100kg.

3.0/3.5/3.8t X series mast:(Pneumatic)

Type	Model	Max. fork height	Overall height						Free lift				Front Overhang		Tilt range F/R (°)	Capacity Load capacity at 500mm					
			Lowered		Extended		Without backrest		With backrest		3t	3.5t/3.8t	Single tire			Dual tire					
			3t	3.5t/3.8t	Without backrest	With backrest	3t	3.5t/3.8t	3t	3.5t/3.8t			3t	3.5t		3.8t	3t	3.5t	3.8t		
																				mm	mm
Wide view mast	XR30/35M250	2500	1804	3267	3342	3645	165	170	165	170	475	480	6/12	3000	3500	3800	3000	3500	3800		
	XR30/35M270	2700	1904	3467	3542	3845	165	170	165	170	475	480	6/12	3000	3500	3800	3000	3500	3800		
	XR30/35M300	3000	2054	3767	3842	4145	165	170	165	170	475	480	6/12	3000	3500	3800	3000	3500	3800		
	XR30/35M330	3300	2204	4067	4142	4445	165	170	165	170	475	480	6/12	3000	3500	3800	3000	3500	3800		
	XR30/35M360	3600	2404	4367	4442	4745	165	170	165	170	475	480	6/12	3000	3500	3800	3000	3500	3800		
	XR30/35M400	4000	2654	4767	4842	5145	165	170	165	170	475	480	6/12	2850	3250	3550	3000	3500	3700		
	XR30/35M430	4300	2804	5067	5142	5445	165	170	165	170	475	480	6/6	2700	3000	3200	2900	3400	3600		
	XR30/35M450	4500	2904	5267	5342	5645	165	170	165	170	475	480	6/6	2550	2850	3100	2850	3350	3550		
	XR30/35M480	4800	3054	5567	5642	5945	165	170	165	170	475	480	6/6	2250	2450	2800	2550	2950	3150		
	XR30/35M500	5000	3154	5767	5842	6145	165	170	165	170	475	480	6/6	2100	2300	2600	2400	2800	3100		
Wide view full free duplex mast	XR30/35M550	5500	3404	6267	6342	6645	165	170	165	170	475	480	3/6	1650	1800	2050	2250	2550	2800		
	XR30/35M600	6000	3654	6767	6842	7145	165	170	165	170	475	480	3/6	1200	1300	1550	2100	2300	2550		
	XR30/35U250	2500	1834	3316	3391	3645	1018	1043	689	789	485.5	490.5	6/12	3000	3500	3800	3000	3500	3800		
	XR30/35U270	2700	1934	3516	3591	3845	1118	1143	789	889	485.5	490.5	6/12	3000	3500	3800	3000	3500	3800		
	XR30/35U300	3000	2084	3816	3891	4145	1218	1243	939	1039	485.5	490.5	6/12	3000	3500	3800	3000	3500	3800		
	XR30/35U330	3300	2234	4016	4091	4445	1318	1343	1089	1189	485.5	490.5	6/12	3000	3500	3800	3000	3500	3800		
	XR30/35U360	3600	2384	4216																	